

Powerzone Technologies Pte Ltd

Generator sets powered by Perkins engine

Prime: 1710KVA/1368KW Standby: 1880KVA/1504KW





Founded in 2009, Powerzone Technologies Pte Ltd specialized in the manufacturing of power generator sets and power plant solutions provider.

Powerzone Technologies is one of the leading power generation solution providers in Singapore, supplying High-Quality generator sets, and spare parts to a wide range of industries worldwide.

Our engines are supplied by the world's largest engine manufacturers, namely Perkins and Cummins as well as Caterpillar, MTU and Mitsubishi.

Designed to provide reliable power even in the most extreme climates and performed above and beyond expectations in ambient testing.

Custom designed and built to reduce service & maintenance costs.

Technical Data	
Generator Set Model: PZ-1710P	
Prime power (kVA/kW)	1710/1368
Standby power (kVA/kW)	1880/1504
Rated voltage line to line (V)	230/400
Rated current (A)	2462.4
Maximum sound level (dBA@7m)	75
Cummins Engine Model: 4012-46TAG3A	
Aspiration	4 Stroke, vee 60°C, turbo charged
Fuel system	Direct injection
Number of cylinders	12
Displacement (L)	45.842
Bore*Stroke (mm)	160x190
Compression ratio	13.6:1
Rated speed (r/min)	1500
Governor	Electric
Engine net weight (kg)	4604
Firing order	1a-6b-5a-2b-3a-4b-6a-1b-2a-5b-4a-3b
Start motor (V)	24
Lubrication System	
Oil capacity (L)	177
Cooling System	
Total coolant capacity (L)	201
Standard Features	
Perkins engine, radiator 50°C max, cooling fans are driven by fan belt, 12V charge alternator	
24V charge alternator, single bearing alternator IP23	
Insulation class H/H, standard auto control system	
Main line circuit breaker / ACB, base fuel tank, 12V batteries, rac and cable	
Exhaust system(Ripple flex exhaust pipe), Exhaust siphon, flange, muffler	
User manual, battery charge	



Powerzone Technologies Pte Ltd

Generator sets powered by Perkins engine

Prime: 1710KVA/1368KW Standby: 1880KVA/1504KW

Options Water heater, alternator heater, PMG, water oil separator, daily fuel tank, remote control panel, One set of air filter, fuel filter, oil filter, Automatic Transfer Switch (ATS), switch box Alternator Model **PI734D** Alternator brand Stamford Phase 3 Voltage (V) 230/400 Wiring type 12 wires 1 Bearing **Power factor 0.8** 50 Frequency (Hz) Prime power (kVA) 1650 **Brushless, self-excitation** Exciter type Voltage regulation (%) ±0.5 **Protection grade IP 23** Insulation grade **Class H Controller-Deepsea** Model **DSE 7320 Comprehensive synchronising & loadsharing** Built-in governor and AVR control Base load (kW export) functionality Mains (utility) de-coupling protection Generator power (kW, kVA) monitoring Overload (kW & kVAR) protection Emergency stop, Auto-Main-Failure (AMF) **Generator Set Dimension (Basic unit)** Open Type L*W*H (mm) : 5500x2250x2355 Weight (kg) : 9500 Silent Type L*W*H (mm): 12032x2352x2898 Weight (kg) : 13500 Warranty **Perkins Engine Powerzone Technologies Pte Ltd** Bik 9, Kallang Place #06-09 12 months from date of delivery. Kallang Basin Industrial Estate Singapore 33915 Tel: +65-6299 3711 Fax: +65-6299 4911 Generator Email : sales@powerzone.com.sg Website : www.powerzone.com.sg 12 months from date of delivery.