

Powerzone Technologies Pte Ltd

Generator sets powered by Perkins engine

Prime: 180KVA/144KW Standby: 200KVA/160KW



POWER THAT NEVER FAILS

Founded in 2009, Powerzone Technologies Pte Ltd specialized in the manufacturing of power generator sets and power plant solutions provider.

Powerzone Technologies is one of the leading power generation solution providers in Singapore, supplying High-Quality generator sets, and spare parts to a wide range of industries worldwide.

Our engines are supplied by the world's largest engine manufacturers, namely Perkins and Cummins as well as Caterpillar, MTU and Mitsubishi.

Designed to provide reliable power even in the most extreme climates and performed above and beyond expectations in ambient testing.

Custom designed and built to reduce service & maintenance costs.

Technical Data	
Generator Set Model: PZ-180P	
Prime power (kVA/kW)	180/144
Standby power (kVA/kW)	200/160
Rated voltage line to line (V)	230/400
Rated current (A)	259.2
Maximum sound level (dBA@7m)	75
Cummins Engine Model: 1106A-70TAG3	
Aspiration	Four-stroke, water-cooled, In line, turbo charged aftercooled
Fuel system	Direct injection
Number of cylinders	6
Displacement (L)	7.01
Bore*Stroke (mm)	105x135
Compression ratio	16:1
Rated speed (r/min)	1500
Governor	Mechanical
Engine net weight (kg)	788
Firing order	1-5-3-6-2-4
Start motor (V)	12
Lubrication System	
Oil capacity	16.5
Cooling System	
Total coolant capacity	21
Standard Features	
Perkins engine, radiator 50°C max, cooling fans are driven by fan belt, 12V charge alternator	
24V charge alternator, single bearing alternator IP23	
Insulation class H/H, standard auto control system	
Main line circuit breaker / ACB, base fuel tank, 12V batteries, rac and cable	
Exhaust system(Ripple flex exhaust pipe), Exhaust siphon, flange, muffler	
User manual, battery charge	



Powerzone Technologies Pte Ltd

Generator sets powered by Perkins engine

Prime: 180KVA/144KW Standby: 200KVA/160KW

Options Water heater, alternator heater, PMG, water oil separator, daily fuel tank, remote control panel, One set of air filter, fuel filter, oil filter, Automatic Transfer Switch (ATS), switch box Alternator **UCI274G** Model Alternator brand Stamford Phase 3 Voltage (V) 230/400 12 wires Wiring type Bearing 1 Power factor 0.8 Frequency (Hz) 50 181.25 Prime power (kVA) Exciter type Brushless, self-excitation ±0.5 Voltage regulation (%) Protection grade **IP 23** Insulation grade **Class H** Controller-Deepsea Model **DSE 6120** Comprehensive synchronising & loadsharing Built-in governor and AVR control Base load (kW export) functionality Mains (utility) de-coupling protection 1 Generator power (kW, kVA) monitoring Overload (kW & kVAR) protection Emergency stop, Auto-Main-Failure (AMF) Generator Set Dimension (Basic unit) Open Type *W*H (mm) <mark>: 2700</mark>*950*1450 t (ka) : Silent Type *W*H (mm) : 3200*1100*1650 10 Weight (kg) : 2400 Warranty **Perkins Engine Powerzone Technologies Pte Ltd** Blk 9, Kallang Place #06-09 12 months from date of delivery. Kallang Basin Industrial Estate Singapore 33915 Tel: +65-6299 3711 Fax: +65-6299 4911

Generator

12 months from date of delivery.

Email : sales@powerzone.com.sg Website : www.powerzone.com.sg