

# Powerzone Technologies Pte Ltd

### **Generator sets powered by Perkins engine**

Prime: 800KVA/640KW Standby: 880KVA/704KW





24V charge alternator, single bearing alternator IP23
Insulation class H/H, standard auto control system

User manual, battery charge

Main line circuit breaker / ACB, base fuel tank, 12V batteries, rac and cable Exhaust system(Ripple flex exhaust pipe), Exhaust siphon, flange, muffler

#### **POWER THAT NEVER FAILS**

Founded in 2009, Powerzone Technologies Pte Ltd specialized in the manufacturing of power generator sets and power plant solutions provider.

Powerzone Technologies is one of the leading power generation solution providers in Singapore, supplying High-Quality generator sets, and spare parts to a wide range of industries worldwide.

Our engines are supplied by the world's largest engine manufacturers, namely Perkins and Cummins as well as Caterpillar, MTU and Mitsubishi.

Designed to provide reliable power even in the most extreme climates and performed above and beyond expectations in ambient testing.

Custom designed and built to reduce service & maintenance costs.

#### **Technical Data**

| Generator Set Model: PZ-800P  |  |  |
|---|--|--|
| Prime power (kVA/kW)  | 800/640                                    |  |
| Standby power (kVA/kW)  | 880/704                                    |  |
| Rated voltage line to line (V)  | 230/400                                    |  |
| Rated current (A)   | 1152                                       |  |
| Maximum sound level (dBA@7m)  | 75   |  |
| Cummins Engine Model: 4006-23TAG3A  |  |  |
| Aspiration  | 4 Stroke, vertical, in line, turbo charged |  |
| Fuel system   | Direct injection                           |  |
| Number of cylinders   | 6  |  |
| Displacement (L)  | 22.921                                     |  |
| Bore*Stroke (mm)  | 160x190                                    |  |
| Compression ratio   | 13.6:1                                     |  |
| Rated speed (r/min)   | 1500                                       |  |
| Governor  | Electric                                   |  |
| Engine net weight (kg)  | 2524                                       |  |
| Firing order  | 1-5-3-6-2-4                                |  |
| Start motor (V)   | 24   |  |
| Lubrication System  |  |  |
| Oil capacity (L)  | 113.4                                      |  |
| Cooling System  |  |  |
| Total coolant capacity (L)  | 105  |  |
| Standard Features   |  |  |
| Perkins engine, radiator 50°C max, cooling fans are driven by fan belt, 12V charge alternator |  |  |



# Powerzone Technologies Pte Ltd

**Generator sets powered by Perkins engine** 

Prime: 800KVA/640KW Standby: 880KVA/704KW

#### Options

Water heater, alternator heater, PMG, water oil separator, daily fuel tank, remote control panel,

One set of air filter, fuel filter, oil filter, Automatic Transfer Switch (ATS), switch box

| Alternator             |                            |
|------------------------|----------------------------|
| Model                  | LV634C                     |
| Alternator brand       | Stamford                   |
| Phase                  | 3                          |
| Voltage (V)            | 230/400                    |
| Wiring type            | 12 wires                   |
| Bearing                | 1                          |
| Power factor           | 0.8                        |
| Frequency (Hz)         | 50                         |
| Prime power (kVA)      | 800                        |
| Exciter type           | Brushless, self-excitation |
| Voltage regulation (%) | ±0.5                       |
| Protection grade       | IP 23                      |
| Insulation grade       | Class H                    |

# Controller-Deepsea

Model

Comprehensive synchronising & loadsharing

**Built-in governor and AVR control** 

Base load (kW export) functionality

Mains (utility) de-coupling protection

Generator power (kW, kVA) monitoring


Overload (kW & kVAR) protection

Emergency stop, Auto-Main-Failure (AMF)


### Generator Set Dimension (Basic unit)

# Open Type

L\*W\*H (mm) : 4200x1950x2050 Weight (kg) : 5000





**DSE 7320** 



### Silent Type

L\*W\*H (mm) : 5300x2150x2500 Weight (kg) : 5800





#### Warranty

Perkins Engine

12 months from date of delivery.

Generator

12 months from date of delivery.

Powerzone Technologies Pte Ltd

Blk 9, Kallang Place #06-09

Kallang Basin Industrial Estate Singapore 33915 Tel: +65-6299 3711 Fax: +65-6299 4911

Email: sales@powerzone.com.sg Website: www.powerzone.com.sg